



型号: (K)WPZ43F (K)WPZ44F  
PN1.6-10.0

### Production enforce standard

Product Specification	Design Spec	Face to Face	Flange End	Test & Check	Pressure-Temp.	Marking
	JB/T 5298	JB/T 5298	JB/T 79	JB/T 5298	GB9131	GB/T 12220
	API6D	API 6D	ANSI B16.5	API 6D	ANSI B16.34	MSS SP-25

### Chief property and specification

PRESSURE		( MPa)				Applicable temperature			Applicable medium	
		SHELL	LEFT	RIGHT	AIR	“G” 型	“D” 型	普通型	“抗硫” 型	“基本” 型
( PNa)	1.6	2.4	1.76	1.76	0.6	-29 ~ 250	-46 ~ 121	-29 ~ 121	含H <sub>2</sub> O和 CO <sub>2</sub> 500Mg/m <sup>3</sup> 的介质	石油 天然气 水等
	2.5	3.75	2.75	2.75	0.6					
	4.0	6.0	4.4	4.4	0.6					
	6.4	9.6	7.04	7.04	0.6					
Lb	150	3.1	2.3	2.3	0.6					
	300	5.52	7.6	5.52	0.6					

### Main Part Material

	Part Material				Part Name
	JB/T7298		API6D		
	WCB	WC6	A352-LCB	A351-CF8M	Body/Bonnet
	2Cr13+ENP	20CrMoV+STL	ANSI410+ENP	ANSI316+ENP	Wedge
	2Cr13	2Cr13	A182-F6a	A182-F316S	Stem
	25+PTFE	20CrMoV+STL	A105+PTFE	A182-F316+PTFE	Seat
	NBR/FPM	Flexible Graphite		PTFE+FPM	Packing
	18-8/柔性石墨/18-8FI				Gasket
	35	35CrMo	A193-B7M	A193-B7M	Bolt
	-29 ~ 250°C	-29 ~ 550°C	-46 ~ 350°C	-46 ~ 200°C	Suitable Temp.
	Water, oil, Steam	Steam, Oil	Steam, Oil	Nitric Acid	Suitable Medium