



规格Size	DN50-DN600
压力Pressure	PN10-PN250
材质Material	1.0619, 1.1138, 1.4306, 1.4308, 1.4408, 1.7706

主要外形连接尺寸 Main external and connection dimension

PN16

DN	50	65	80	100	125	150	200	250	300	350	400	450	500	600
L	230	290	310	350	400	480	600	730	850	980	1100	1200	1250	1450
H	140	148	175	190	210	235	308	350	390	430	468	495	530	615
W(kg)	12	19	25	35	49	76	108	185	310	400	450	-	830	1300

PN25

DN	50	65	80	100	125	150	200	250	300	350	400	450	500	600
L	230	290	310	350	400	480	600	730	850	980	1100	1200	1250	1450
H	150	162	180	202	215	245	315	360	395	438	473	505	542	628
W(kg)	12	19	25	35	49	76	108	185	310	400	450	-	830	1300

PN40

DN	50	65	80	100	125	150	200	250	300	350	400	450	500
L	230	290	310	350	400	480	600	730	850	980	1100	1200	1250
H	160	175	185	220	250	270	350	410	430	520	560	590	620
W(kg)	13	20	26	39	62	88	135	200	350	430	530	-	950

PN64

DN	50	65	80	100	125	150	200	250	300	350	400
L	300	340	380	430	500	550	650	775	900	1025	1150
H	178	198	215	250	295	330	385	445	475	515	615
W(kg)	32	41	49	68	100	139	225	311	580	-	-

PN100

DN	50	65	80	100	125	150	200	250	300	350	400
L	300	340	380	430	500	550	650	775	900	1025	1150
H	210	225	275	308	645	405	435	485	505	548	632
W(kg)	33	45	56	74	110	156	240	325	650	-	-