



产品执行标准 Production enforce standard

结构形式 Structural formation	BB-BG-OS & Y
驱动方式 Driving maner	手动 Hand-operated
	电动 Electric-actuated
设计标准 Design standard	DIN3356
结构长度 Face to face	DIN3202
连接法兰 Flange ends	DIN2543-2545
实验和检验 Test & inspection	DIN3230

注:系列阀门连接法兰可根据用户要求设计制造。

Notes: The size of serial, valve connecting flange can design according to customers reuirment.

产品性能规范Chief property and specification

公称压力(MPa) Nominal pressure	壳体试验压力(MPa) Shell test	密封试验压力(MPa) Sealing test	适用温度(°C) Suitable temp	适用介质 Applicable medium
1.6	2.4	1.76	-110~600°C	水、蒸汽、油品等 Water oil & gas
2.5	3.75	2.75		
4.0	6.0	4.4		
6.4	9.6	7.04		

主要零部件材料Main Part Material

壳体 Body	GS-C25								1.4308			
阀瓣 Disc	GS-C25			1.4308		1.4408		Monel		1.4308		
阀杆 Stem	13Cr			1.4308		1.4408		Monel		1.4308		
阀瓣密封面 Wedge disc sealing face	13Cr	13Cr	STL	1.4308	STL	1.4408	STL	Monel	1.4308	1.4308	STL	
阀座密封面 Seating sealing face	13Cr	STL	STL	1.4308	STL	1.4408	STL	Monel	1.4308	STL	STL	
壳体 Body	1.4408				1.4306				1.4301			
阀瓣 Disc	1.4408				1.4306				1.4301			
阀杆 Stem	1.4408				1.4306				1.4301			
阀瓣密封面 Wedge disc sealing face	1.4408	1.4408	STL	1.4306	1.4306	STL	1.4301	1.4301	STL	STL		
阀座密封面 Seating sealing face	1.4408	STL	STL	1.4306	STL	STL	1.4301	STL	STL	STL		